


The logic of information exchange

Floris Roelofsen

based on joint work with Ivano Ciardelli



LoLaCo lecture, Amsterdam, October 27, 2014

Motivation

Our general goal

- A logical framework to model **information exchange** through communication between a number of agents

Starting point: epistemic logic

- Allows us to model what the **facts** are in a given situation and what all the agents **know** about these facts and about each other
- Allows us to capture the **informative content** of sentences

Motivation

Our general goal

- A logical framework to model **information exchange** through communication between a number of agents

Starting point: epistemic logic

- Allows us to model what the **facts** are in a given situation and what all the agents **know** about these facts and about each other
- Allows us to capture the **informative content** of sentences

What is missing in this basic framework?

Motivation

What is missing?

- It is not only important to model what the agents know, but also what they **want to know**, i.e., the **issues** that they entertain

Motivation

What is missing?

- It is not only important to model what the agents know, but also what they **want to know**, i.e., the **issues** that they entertain

Moreover:

- Agents do not only use **declarative** sentences to **provide information**
- They also use **interrogative** sentences to **request information**
- To capture the meaning of both declaratives and interrogatives, we need to be able to capture both **informative** and **inquisitive** content

Motivation

Summing up

- Epistemic models need to be enriched with **issues**
- Our logical language needs to be enriched with **interrogatives**
- Our notion of meaning needs to be enriched with **inquisitive content**

Epistemic logic

Epistemic models

An epistemic model is a triple $M = \langle \mathcal{W}, V, \{\sigma_a \mid a \in A\} \rangle$, where:

- \mathcal{W} is a set of **possible worlds**
- $V : \mathcal{W} \rightarrow \wp(\mathcal{P})$ is a **valuation function**
- $\sigma_a(w) \subseteq \mathcal{W}$ is the **information state** of agent a in w

Epistemic logic

- The language \mathcal{L}_{EL} is a propositional language enriched with **knowledge modalities** K_a .
- The semantics is given by a recursive definition of **truth w.r.t. a world**.
- The **proposition** expressed by a sentence φ in a model M is the set of worlds where the sentence is true:

$$|\varphi|_M = \{w \in \mathcal{W} \mid \langle M, w \rangle \models \varphi\}$$

- An agent **knows** φ iff φ is **true in all worlds** in the agent's info state:

$$\langle M, w \rangle \models K_a \varphi \iff \text{for all } v \in \sigma_a(w), \langle M, v \rangle \models \varphi$$

- Notice that K_a expresses a **relation between two sets of worlds**: a 's information state and the proposition expressed by φ

$$\langle M, w \rangle \models K_a \varphi \iff \sigma_a(w) \subseteq |\varphi|_M$$

Modeling issues

How to model issues?

- We want to equip agents not only with an information state, but also with an **inquisitive state** that describes the **issues** that they entertain.
- But how to model issues?

Key idea

- An issue can be modeled as a **set of information states**
- Namely, those information states in which the issue is **resolved**

Example

- The issue **'who won the elections'** is modeled as the set of information states in which it is known who won the elections

Two constraints

Does any set of information states properly represent an issue?

– No, there are **two constraints**.

Issues are downward closed

- If an issue I is resolved in an information state s , then it will also be resolved in any **more informed** information state $t \subset s$
- So issues are **downward closed**: for any $s \in I$, if $t \subset s$, then $t \in I$


Issues always contain the inconsistent information state

- The **inconsistent information state** is the empty state, \emptyset
- It is standardly assumed that in \emptyset **everything is known**
- Similarly, we assume that in \emptyset **every issue is resolved**
- This means that an issue always contains \emptyset
- Equivalently, issues are always **non-empty** sets of info states

Definition of issues and examples

Issues

- An issue is a **non-empty, downward closed** set of information states.
- We say that an issue I is an issue **over a state s** in case $s = \bigcup I$.
- The set of all issues is denoted by Π .
- If we depict an issue, we only depict its **maximal elements**.




Four issues over the state $\{w_1, w_2, w_3, w_4\}$.

Inquisitive epistemic models

A model should now provide, for every possible world w :

1. a specification $V(w)$ of the basic facts;
2. a specification $\sigma_a(w)$ of the agents' information;
3. a specification $\Sigma_a(w)$ of the agents' issues.

where $\Sigma_a(w)$ should be an issue over $\sigma_a(w)$.



Inquisitive epistemic models

Can we simplify?

- Do we need to specify all three components explicitly?
- Recall that $\Sigma_a(w)$ should be an issue over $\sigma_a(w)$.
- But this means that $\sigma_a(w) = \bigcup \Sigma_a(w)$.
- So if we know $\Sigma_a(w)$, we also know $\sigma_a(w)$.
- This means that $\sigma_a(w)$ does not need to be specified explicitly.
- $\Sigma_a(w)$ **already encodes both information and issues.**

Definition of inquisitive epistemic models

Inquisitive epistemic models

An **inquisitive epistemic model** is a triple $M = \langle \mathcal{W}, V, \{\Sigma_a \mid a \in A\} \rangle$, where:

- \mathcal{W} is a set of **possible worlds**
- $V : \mathcal{W} \rightarrow \wp(\mathcal{P})$ is a **valuation function**
- $\Sigma_a(w) \in \Pi$ is the **inquisitive state** of agent a in w

For any w , $\sigma_a(w) := \bigcup \Sigma_a(w)$ is the **information state** of a at w .

Enriching the logical language

- We have enriched our epistemic models with **issues**
- The next step is to enrich our logical language with **interrogatives**

Syntax

- **Declaratives:** $\alpha ::= p \mid \perp \mid \alpha \wedge \alpha \mid \alpha \rightarrow \alpha \mid K_a \varphi \mid E_a \varphi$
- **Interrogatives:** $\mu ::= ?\{\alpha_1, \dots, \alpha_n\} \mid \mu \wedge \mu \mid \alpha \rightarrow \mu$

Abbreviations

- $\neg \alpha := \alpha \rightarrow \perp$
- $\alpha \vee \beta := \neg(\neg \alpha \wedge \neg \beta)$
- $? \alpha := ?\{\alpha, \neg \alpha\}$

Examples

- $K_a ? K_b ? p$
- $p \rightarrow ? K_b p$
- $K_a ? p \rightarrow ? K_b K_a ? p$

From truth conditions to support conditions

- We have enriched our **models** and our **logical language**.
- Next, we need to enrich the **semantics**.
- In EL, the semantics specifies **truth conditions** wrt worlds.
- For **interrogatives**, this does not work.
- Rather, we should give **resolution conditions** wrt information states.
- We could give a simultaneous definition of truth and resolution.
- But there is a better solution: we will **lift** the interpretation of declarative sentences from worlds to information states as well.
- We define a **support** relation, $s \models \varphi$, where intuitively:
 - $s \models \alpha$ amounts to: α is **established**, or **true everywhere** in s ;
 - $s \models \mu$ amounts to: μ is **resolved** in s .

Support conditions

Definition (Support)

1. $\langle M, s \rangle \models p \iff p \in V(w)$ for all worlds $w \in s$
2. $\langle M, s \rangle \models \perp \iff s = \emptyset$
3. $\langle M, s \rangle \models ?\{\alpha_1, \dots, \alpha_n\} \iff \langle M, s \rangle \models \alpha_i$ for some $i \in \{1, \dots, n\}$
4. $\langle M, s \rangle \models \varphi \wedge \psi \iff \langle M, s \rangle \models \varphi$ and $\langle M, s \rangle \models \psi$
5. $\langle M, s \rangle \models \alpha \rightarrow \varphi \iff$ for any $t \subseteq s$, if $\langle M, t \rangle \models \alpha$ then $\langle M, t \rangle \models \varphi$
6. $\langle M, s \rangle \models K_a \varphi \iff$ for any $w \in s$, $\langle M, \sigma_a(w) \rangle \models \varphi$
7. $\langle M, s \rangle \models E_a \varphi \iff$ for any $w \in s$ and for any $t \in \Sigma_a(w)$, $\langle M, t \rangle \models \varphi$

Fact (Persistence, empty state)

- **Persistence:** if $\langle M, s \rangle \models \varphi$ and $t \subseteq s$ then $\langle M, t \rangle \models \varphi$.
- **Empty state:** $\langle M, \emptyset \rangle \models \varphi$ for any sentence φ .

Deriving truth conditions from support conditions

Definition (Truth)

φ is defined to be **true at a world w** , $\langle M, w \rangle \models \varphi$, just in case $\langle M, \{w\} \rangle \models \varphi$

Fact (Truth conditions)

1. $\langle M, w \rangle \models p \iff p \in V(w)$
2. $\langle M, w \rangle \not\models \perp$
3. $\langle M, w \rangle \models ?\{\alpha_1, \dots, \alpha_n\} \iff \langle M, w \rangle \models \alpha_i$ for some index $1 \leq i \leq n$
4. $\langle M, w \rangle \models \varphi \wedge \psi \iff \langle M, w \rangle \models \varphi$ and $\langle M, w \rangle \models \psi$
5. $\langle M, w \rangle \models \alpha \rightarrow \varphi \iff \langle M, w \rangle \not\models \alpha$ or $\langle M, w \rangle \models \varphi$
6. $\langle M, w \rangle \models \neg\alpha \iff \langle M, w \rangle \not\models \alpha$
7. $\langle M, w \rangle \models \alpha \vee \beta \iff \langle M, w \rangle \models \alpha$ or $\langle M, w \rangle \models \beta$
8. $\langle M, w \rangle \models K_a\varphi \iff \langle M, \sigma_a(w) \rangle \models \varphi$
9. $\langle M, w \rangle \models E_a\varphi \iff$ for any $t \in \Sigma_a(w)$, $\langle M, t \rangle \models \varphi$

Inquisitive epistemic logic

Definition (Proposition)

The **proposition** expressed by φ in M is the set $[\varphi]_M = \{s \mid \langle M, s \rangle \models \varphi\}$.

Definition (Truth-set)

The **truth-set** of φ in M is the set of worlds $|\varphi|_M = \{w \mid \langle M, w \rangle \models \varphi\}$.

Fact (Truth-sets and propositions)

For any φ and any M :

$$|\varphi|_M = \bigcup [\varphi]_M$$

Truth for declaratives and interrogatives

Truth for declaratives

- The semantics of a declarative is **determined by its truth conditions**:

$$\langle M, s \rangle \models \alpha \iff \text{for all } w \in s, \langle M, w \rangle \models \alpha$$

- Thus, for any declarative α we have $[\alpha]_M = \wp(|\alpha|_M)$.


Truth for interrogatives

- $\langle M, w \rangle \models \mu$ just in case $w \in s$ for some state s that supports μ .
- That is, μ is true at a world just in case it can be **truthfully resolved**.

Back to the support conditions: basic cases

Definition

1. $\langle M, s \rangle \models p \iff p \in V(w)$ for all worlds $w \in s$
2. $\langle M, s \rangle \models \perp \iff s = \emptyset$
3. $\langle M, s \rangle \models ?\{\alpha_1, \dots, \alpha_n\} \iff \langle M, s \rangle \models \alpha_i$ for some index $1 \leq i \leq n$
4. $\langle M, s \rangle \models \varphi \wedge \psi \iff \langle M, s \rangle \models \varphi$ and $\langle M, s \rangle \models \psi$




[p]



[?p]



[p ∧ q]



[?p ∧ ?q]


Support for implication

Definition


- $\langle M, s \rangle \models \alpha \rightarrow \varphi \iff$ for any $t \subseteq s$, if $\langle M, t \rangle \models \alpha$ then $\langle M, t \rangle \models \varphi$

Fact

- $\langle M, s \rangle \models \alpha \rightarrow \varphi \iff \langle M, s \cap |\alpha|_M \rangle \models \varphi$



$[p \rightarrow q]$



$[p \rightarrow ?q]$

The knowledge modality


General definition

- $\langle M, w \rangle \models K_a \varphi \iff \langle M, \sigma_a(w) \rangle \models \varphi$


Knowing a declarative

For a declarative α , support amounts to truth at each world, so in this case we recover the **standard clause**:


- $\langle M, w \rangle \models K_a \alpha \iff$ for all $v \in \sigma_a(w)$, $\langle M, v \rangle \models \alpha$



$\Sigma_a(w_{11})$



$[p]$



$[q]$

The knowledge modality



General definition

- $\langle M, w \rangle \models K_a \varphi \iff \langle M, \sigma_a(w) \rangle \models \varphi$

Knowing an interrogative

- $\langle M, w \rangle \models K_a \mu \iff \sigma_a(w)$ resolves μ .

Example: $K_a ?p \equiv K_a p \vee K_a \neg p$




The entertain modality

General definition


- $\langle M, w \rangle \models E_a \varphi \iff$ for any $t \in \Sigma_a(w)$, $\langle M, t \rangle \models \varphi$

Declaratives and interrogatives

- For a declarative α , $E_a \alpha \equiv K_a \alpha$.
- For an interrogative μ , $E_a \mu$ is true just in case whenever the internal issues of a are resolved, μ is also resolved.
- Intuitively, $E_a \mu$ is true iff every state that a **wants to reach** is one that **supports** μ



$\Sigma_a(w_{11})$



$[?q]$



$[?p]$

Wondering = entertaining without knowing


- The truth conditions for $E_a\mu$ are close to those for **a wonders about μ**
- But **one exception**: if a already **knows** how to resolve μ , $E_a\mu$ is true but we would not say that a wonders about μ .
- So to **wonder** about μ is to **entertain μ without knowing μ** .

$$W_a\varphi := E_a\varphi \wedge \neg K_a\varphi$$


- With this definition, $W_a\varphi$ is a **contradiction** if φ is a **declarative**.



$\Sigma_a(w_{11})$



[?q]



[?p]

Comparison with basic EL: the modalities

- Our operators K_a and E_a are **not Kripke modalities**.
- However, like Kripke modalities in epistemic logic, they express a **relation between two semantic objects of the same type**:
 - a **state** associated with the world
 - the **proposition** expressed by the prejaçant
- In EL, states $\sigma_a(w)$ and propositions $|\varphi|_M$ are simple sets of worlds:
 - $\langle M, w \rangle \models K_a \varphi \iff \sigma_a(w) \subseteq |\varphi|_M$
- In IEL, both states $\Sigma_a(w)$ and propositions $[\varphi]_M$ are more structured, namely, they are issues.
 - $\langle M, w \rangle \models K_a \varphi \iff \bigcup \Sigma_a(w) \in [\varphi]_M$
 - $\langle M, w \rangle \models E_a \varphi \iff \Sigma_a(w) \subseteq [\varphi]_M$

Comparison with basic EL: the logic

IEL is a conservative extension of EL

- Any IE-model M induces a standard epistemic model M^e , obtained simply by **forgetting the issues** for each agent.
- For any IE-model M and formula $\alpha \in \mathcal{L}_{EL}$,

$$M, w \models \alpha \iff M^e, w \models \alpha$$

Conclusion

- Our goal was to develop a logic to model **information exchange**, seen as a process of raising and resolving issues.
- We enriched epistemic models with **issues**.
- We enriched the logical language with **interrogatives**.
- We formulated a uniform, **support-based semantics** for declaratives and interrogatives.
- The result is a **conservative extension** of standard epistemic logic.
- K_a was generalized to describe which issues agents can **resolve**.
- We introduced new modalities E_a and W_a to describe which issues agents **entertain** and **wonder about**.

Some references

Inquisitive semantics: a new notion of meaning

Ivano Ciardelli, Jeroen Groenendijk, and Floris Roelofsen.
Language and Linguistics Compass, 2013.

Inquisitive dynamic epistemic logic

Ivano Ciardelli and Floris Roelofsen. Synthese, 2014.

Axiomatizing inquisitive epistemic logic

Ivano Ciardelli. Advances in modal logic, 2014.

`www.illc.uva.nl/inquisitivesemantics`